

Tripp Lite

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

# Keyspan Mini DisplayPort 1.2 to VGA/DVI/HDMI Adapter, 4K x 2K HDMI @ 24/30 Hz, Thunderbolt 1/2, White

#### MODEL NUMBER: P137-06N-HDV4KW











Passive Mini DP to HDMI/VGA/DVI adapter connects your Mini DP or Thunderbolt 1/2 laptop to a VGA, DVI or HDMI display.

#### **Features**

# Passive Adapter Connects a Mini DisplayPort Device to a VGA, DVI or HDMI Display

No more carrying around separate adapters for various monitors, projectors and televisions. This Keyspan® Mini DP to HDMI/VGA/DVI adapter connects a VGA, DVI or HDMI display to the Mini DisplayPort or Thunderbolt 1/2 port on your Chromebook, MacBook, Microsoft Surface or other compatible laptop or tablet. Only one display can be connected at a time.

#### Simple All-in-One Solution for Displaying 4K Video on a Large Screen

The P137-06N-HDV4KW is ideal for classrooms, lecture halls and anywhere else you may need to connect to a monitor. Just connect the converter between your laptop and a VGA, DVI or HDMI display. You no longer have to dig around in your laptop bag for the correct adapter to match the display.

## Transmits Crystal-Clear Video up to 4K x 2K for Ultra HD Presentations

This all-in-one unit features separate female HD15, DVI and HDMI ports. The HD15 port supports high-definition video resolutions up to  $1920 \times 1200$ , including 1080p. The DVI-I dual-link port supports HD resolutions up to  $1920 \times 1080$  (1080p). The HDMI port supports Ultra HD 4K x 2K video ( $3840 \times 2160$ ) at 24/30 Hz, as well as 36-bit Deep Color (12 bits per channel). The HDMI port is backward compatible with non-4K displays.

#### Passive Adapter for Use with Dual-Mode DisplayPort Sources

The P137-06N-HDV4KW is a passive adapter that requires the connected computer to support DisplayPort++ (DP++). This allows HDMI and DVI signals to be passed through. Check the documentation for your Mini DisplayPort source for compatibility.

## Ready to Use Right from the Package, So You Can Plug and Play Immediately

The plug-and-play adapter requires no software, drivers or external power, works with both Windows and Mac operating systems, and is compatible with laptops, tablets and other devices equipped with a female Mini DisplayPort or Thunderbolt 1/2 port. With its small size and built-in cable, the P137-06N-HDV4KW is recommended for stowing in your laptop bag and carrying to school or the office.

## 3-Year Warranty

The P137-06N-HDV4KW is backed by a 3-year warranty, ensuring reliability and performance.

## **Highlights**

- Multiple video outputs connect to most displays—no more carrying multiple adapters
- HDMI port delivers UHD quality at resolutions up to 3840 x 2160 (4K x 2K) @ 24/30 Hz
- Compact unit fits easily into briefcase or laptop bag for instant use anywhere
- Plug-and-play operation with no software required for easy, immediate installation
- Passive adapter requires connected computer to have DP++ port for signal passthrough

#### **Applications**

- Connect your laptop to an HDMI, VGA or DVI monitor in a lecture hall or conference room for a video presentation
- Add a secondary monitor to the PC or laptop in your office or home workspace

#### **System Requirements**

- Source device with Thunderbolt
   1/2 output or Mini DisplayPort
   that supports DP++
- Display device with VGA, DVI or HDMI input

#### Package Includes

 P137-06N-HDV4KW Keyspan Mini DisplayPort 1.2 to VGA/DVI/HDMI All-in-One Converter Adapter, White



• Quick Start Guide

# **Specifications**

OVERVIEW	
UPC Code	037332210630
Technology	DVI (all types); HDMI (All types); VGA/SVGA; DisplayPort (all types)
INPUT	
Cable Length (in.)	6
PHYSICAL	
Shipping Dimensions (hwd / in.)	0.910 x 5.400 x 4.000
Shipping Dimensions (hwd / cm)	2.31 x 13.72 x 10.16
Shipping Weight (lbs.)	0.2000
Shipping Weight (kg)	0.09
Color	White
ENVIRONMENTAL	
Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 176 F (-10 to 80 C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
CONNECTIONS	
Side A - Connector 1	MINI DISPLAYPORT (MALE)
Side B - Connector 1	DVI-I DUAL LINK (FEMALE)
Side B - Connector 2	HD15 (FEMALE)
Side B - Connector 3	HDMI (FEMALE)
CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>