

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIALS:

1.1 HOUSING & NUT: PASSIVATED STAINLESS STEEL

1.2 CENTER CONTACT: GOLD BERYLLIUM COPPER

1.3 DIELECTRIC: PTFE FLUOROCARBON

2. ELECTRICAL SPECIFICATIONS:

2.1 FREQUENCY RANGE: DC TO 18.0 GHz

2.2 VSWR (MAX):

DC TO 4.0 GHz: 1.04:1 4.0 TO 8.0 GHz: 1.07:1 8.0 TO 18.0 GHz: 1.12:1 2.3 IMPEDANCE: 50 OHMS

EMERSON.	3RD ANGLE PROJECTION	Midwest Microwave			
Network Power Connectivity Solutions This PROPRIETARY Document is properly of Immerson Network. It is confidential in nature, In it is confidential in nature, on transferate, and issued without permission and is returnable upon demand. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.	RoHS 2002/95/EC	Title: SMA PLUG TO TYPE N JACK ADAPTER			
	UNLESS OTHERWISE SPECIFIED UNITS: INCH .XX ±.02 .XXX ±.005 ANGLES ±2°	Model No. ADT-2582-NF-SMM-02			
		Size	DO NOT SCALE DRAWING	Date: 7/23/2013	Sheet 1 of 1